



OPERATIONS

Loader Arms ... Radial Operating Wt. ... 11265 lbs Rated Oper. Cap. @ 35% ... 3535 lbs Rated Oper. Cap. @ 50% ... 5050 lbs **Ground Pressure** ... 4.4 psi **Engine Power** ... 120 hp **Tipping Load** ... 10100 lbs Max. Travel Speed ... 10 mph Height to Bkt Pin ... 125 in. Dump hgt @ Bkt Discharge ... 91 in. Rear Angle of Departure ... 34 deg. Bkt Roll Back @ Ground Lev. ... 45 deg. **Ground Clearance** ... 15 in. Overall Length w/ Bkt ... 157 in. Reach @ Dump Hgt. ... 24 in.





SERVICE CAPACITY

Fuel Tank 30 gal
Hydraulic Tank 22 gal
Engine Coolant 5.5 gal
Engine Oil (Incl. Filter) 12 quarts

COMFORT



- SJC for easy, intuitive operation.
- Pressurized cab for clean operating environment.
- $\bullet\,$ Optional all–weather cab with heat & AC.

POWER

- Cummins 3.8 liter turbocharged diesel engine
- 120 hp
- 360 foot-pounds of torque





PERFORMANCE

- ASV's patented Posi-Track® rubber track suspension
- fully-flexible track & suspended wheels
- 15 in. ground clearance



ELECTRICAL SYSTEM

Features Upgradeable Wiring Harness, Attch

Ctrl Kit, Block Heater, Backup

Camera

Normal Charge 12V

Battery 950 CCa

Alternator Charging System 120 Amp

Port Outlet (In cab) 1–12 V



